Asserta Mini sounder

The Asserta Mini sounder is a versatile, compact unit that has been designed for industrial environments or areas where there is a requirement for a robust alarm. Available for use in a wide range of fire and process systems.



Technical specification

Voltage	9 - 60Vdc
	110 - 230Vac
Current	13mA @ 24Vdc (Typical Tone 3)
	20mA @ 230Vac (Typical Tone 3)
Sound output	105dB (Typical Tone 3)
Tones	32
Alarm stages	2
Monitoring	Reverse Polarity (dc version)
Temperature	- 25°C to + 70°C
Protection	IP66
Construction	ABS
Weight	0.30Kg (dc version)
	0.36Kg (mains version)
Colour	Red or grey

Features

- 32 tones
- Wide operating voltage
- IP66 protection
- Compact enclosure

Benefits

- Ideal for all general signalling applications
- Adaptable to all types of installation

Reference	Catalogue No.	Description
AS/N/S/9-60V/R	7061154FUL-0105	Asserta Mini Sounder, Red, 9 to 60Vdc
AS/N/S/9-60V/G	7092269FUL-0146	Asserta Mini Sounder, Grey, 9 to 60Vdc
AS/N/110-230/R	7063134FULL-0155	Asserta Mini Sounder, Red, 110 to 230Vac
AS/N/SV/S/110-230V/G	7092268FUL-0145	Asserta Mini Sounder, Grey, 110 to 230Vac
AS/M/S/115-230/G	7092267FUL-0144	Asserta Mini Sounder, Grey, 115 to 230Vac
AS/S/115-230/G/120	7092274FUL-0151	Asserta Mini Sounder, Grey, 115 to 230Vac

Powering Business Worldwide